



UK DECLARATION OF CONFORMITY  TLX Silver  MFTLXSILVERUKCPR			
Unique identification code of the product-type:	TLX Silver		
Type, batch or serial number or any other element allowing identification of the construction product	See product		
Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	BS EN 13984:2013 Flexible sheets for waterproofing. Plastic and rubber vapour control layers. Definitions and characteristics		
Manufacturer	Web Dynamics Ltd. Moss Lane Blackrod Bolton Lancashire BL5 5JB		
System of AVCP	System 3		
UK Assessment Body	BTTG (NB 0338) performed ITT under system 3 and issued test reports		





Essential Characteristics		Performance	
Property	Standard	Nominal	Notified body
Water tightness	EN 1928:2000, Method A	W1	BTTG
Resistance to impact	EN 12691	NPD	-
Water vapour resistance after artificial ageing resistance	EN 1296 (artificial ageing) EN 1931	Sd >74.05m* μ>300,000*	BTTG
Chemical resistance	EN 1847	NPD	-
Resistance to tearing	12310-1	MD: 167N CD: 217N	BBA
Joint Strength	EN 12317-2	NPD	-
Water vapour resistance	EN 1931	Sd >66.70m* μ>300,000*	BTTG
Tensile Properties	EN 12311-2	MD: 510N/50mm CD: 470N/50mm	BTTG
Reaction to fire	EN 13501- 1:2007+A1:2009	Class D	BTTG
Dangerous substances	-	NPD	-

<sup>\*</sup> Figure quoted for 1 external, reflective layer (WEB 1B) only. Actual product performance will be greater than this due to 2nd outer layer and 4 metalised internal layers

Signed for and on behalf of the manufacturer by:

**Thomas Hunt** 

United Kingdom 05/03/2021

**Managing Director** 

First signed 05/03/2021